Pharmacy Plus Bluetooth Enabled Refrigerator

400L Pharmacy Plus Upright Fridge with Solid Door

Product code	PPSR400BT
SKU code	444411317



Key features

- ✓ Temperature range of +2°C to +8°C
- ✓ Audible and visual temperature alarms

- \checkmark Solid and glass door options
- ✓ Integrated lock, supplied with 2 keys for added security



Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.



Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.



Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



www.lec-medical.co.uk \$ 0344 815 3742

Specification: 400L Pharmacy Plus Upright Fridge with Solid Door

SKU Code Product Code	444411317 PPSR400BT
Gross Capacity (litres)	394L
Net Capacity (litres)	394L 389L
Jnit External Width (mm)	595mm
Jnit External Wigth (mm) Jnit External Depth (mm)	600mm
Init External Height (mm)	1925mm
Product Weight (kg)	65.6kg
Packed Width (mm)	640mm
Packed Depth (mm)	635mm
Packed Height (mm)	1995mm
Packed Weight (kg)	72.5kg
Country of Origin	UK
nternal Dimensions (mm) (WxDxH)	500mm x 480mm x 1775mm
Temperature Range	+2°C to +8°C
	White/green
External Finish	Painted Steel
nternal Finish	HIPS*
ype of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / HIPS*
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Dpen Door Sensor	Yes
lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Femperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
/isual Alarms	Yes
Number of Shelves/Drawers	7
Number of Shelf Positions	12
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Size 2 (mm) (WxDxH)	493mm x 265mm x 6mm
Shelf Material	White Polythene Coated Wire
Drawer Size (mm) (WxDxH)	2@ 408mm x 405mm x 195mm
Drawer Size 2 (mm) (WxDxH) Drawer Material	N/A N/A
Number of Baskets	1V/A
	I N/bita Daluthana Castad M/iva
Basket Material	White Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
nterior Light	Yes LED
ight Type	
light Activation	Door Switch / Controller
Fan Drawle France	Yes - Tangential
Spark Free	No Auto (Off Curls)
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	Yes/48hrs
Bluetooth	Yes
Number of Probes	2
Probe Type	Air & Load (Silicone Oil)
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a/38g
JK 3 Pin Plug	Yes
Other Plug Types Available	No
/oltage Supply	220-240V
Frequency (Hz)	50Hz
Max Power (W)	88W
Max Current Rating (A)	0.65A
Energy Consumption (kWh/24h)	1.17kWh/24h
Energy Consumption AE (kWh)	427.05kWh
Noise Level (dB)	40.3dB
nsulation Thickness (mm)	45mm
nsulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane

The Experts in Medical Refrigeration

www.lec-medical.co.uk © 0344 815 3742

