# Pharmacy Plus Bluetooth Enabled Refrigerator

#### 158L Pharmacy Plus Undercounter Fridge with Solid Door – Digital Lock

Product code PPSR158BT-DLK

SKU code 444411389









#### Key features

- √ Temperature range of +2°C to +8°C
- √ Audible and visual temperature alarms
- √ Solid and glass door options
- √ Multiple shelf positions for flexible storage solutions











## Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

## Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

## Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

## Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

#### Digital Lock

This model has an integrated digital lock for added security and access control



SKU Code	444411389
Product Code	PPSR158BT-DLK
Gross Capacity (litres)	158L
Net Capacity (litres)	154L
Unit External Width (mm)	595mm
Unit External Depth (mm)	600mm
Unit External Height (mm)	850mm
Product Weight (kg)	34.79kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	910mm
Packed Weight (kg)	39.10kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	495mm x 480mm x 720mm
Temperature Range	+2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
<u>Door Finish</u>	Painted Steel / HIPS*
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm) Replacement Door Seal	1150mm
_ ·	Yes
Open Door Sensor	Yes Digital Legis
Lock	Digital Lock 4 All adjustable
Adjustable Feet (number & position)  Porthole	4 Ali adjustable Yes
Porthole Size	16mm
Porthole Size Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Visual / Marris	
Number of Shelves/Drawers	
Number of Shelves/Drawers Number of Shelf Positions	4 5
Number of Shelf Positions	4 5
Number of Shelf Positions Shelf Size (mm) (WxDxH)	4
Number of Shelf Positions	4 5 496mm x 405mm x 6mm
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle)
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil)
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h 182.5kWh
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A 1 Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h 182.5kWh 40.1dB
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h 182.5kWh 40.1dB 45mm
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Type	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h 182.5kWh 40.1dB 45mm High Density Polyurethane Foam
Number of Shelf Positions Shelf Size (mm) (WxDxH) Shelf Size 2 (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	4 5 496mm x 405mm x 6mm 493mm x 265mm x 6mm White Polythene Coated Wire N/A N/A N/A N/A N/A Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / App Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.59kWh/24h 182.5kWh 40.1dB 45mm

