Pharmacy Plus Bluetooth Enabled Refrigerator

400L Pharmacy Plus Upright Fridge with Glass Door – Digital Lock

Product code PPGR400BT-DLK

SKU code 444411395









Key features

- √ Temperature range of +2°C to +8°C
- ✓ Audible and visual temperature alarms
- √ Solid and glass door options
- ✓ Multiple shelf locations provide flexible storage solutions.











Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Digital Lock

This model has an integrated digital lock for added security and access control



CVII Codo	/, /, /, /, IIZOE
SKU Code Product Code	444411395 PPGR400BT-DLK
Gross Capacity (litres)	394L
Net Capacity (litres)	389L
Unit External Width (mm)	595mm
Unit External Depth (mm)	600mm
Unit External Height (mm)	1925mm
Product Weight (kg)	73.4kg
Packed Width (mm)	640mm
Packed Depth (mm)	635mm
Packed Height (mm)	1995mm
Packed Weight (kg)	80.3kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	500mm x 480mm x 1775mm +2°C to +8°C
Temperature Range Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	PVC / Glass
Door Type	Glass
Door Style	Hinged, Right Hand, Non-Reversible
Door Liner	N/A
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Digital Lock
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location Temperature Display on Panel	Rear Bottom (Right) Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	7
Number of Shelf Positions	12
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Size 2 (mm) (WxDxH)	493mm x 265mm x 6mm
Shelf Material	White Polythene Coated Wire
Shelf Material Drawer Size (mm) (WxDxH)	White Polythene Coated Wire N/A
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH)	White Polythene Coated Wire N/A N/A
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material	White Polythene Coated Wire N/A
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets	White Polythene Coated Wire N/A N/A N/A N/A 1
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH)	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH)	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle)
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil)
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	White Polythene Coated Wire N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W)	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption AE (kWh)	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W 0.65A 1.61kWh/24h 587.65kWh
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption AE (kWh) Noise Level (dB)	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W 0.65A 1.61kWh/24h 587.65kWh 40.3dB
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W 0.65A 1.61kWh/24h 587.65kWh 40.3dB 45mm
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Type	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W 0.65A 1.61kWh/24h 587.65kWh 40.3dB 45mm High Density Polyurethane Foam
Shelf Material Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	White Polythene Coated Wire N/A N/A N/A N/A N/A 1 White Polythene Coated Wire 485mm x 255mm x 171mm Yes LED Door Switch / Controller Yes - Tangential No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/38g Yes No 220-240V 50Hz 88W 0.65A 1.61kWh/24h 587.65kWh 40.3dB 45mm

