Pharmacy Plus Bluetooth

Enabled Refrigerator

158L Pharmacy Plus Undercounter Fridge with Glass Door – Left Hand Hinged

Product code PPGR158BT-LHH-UK

SKU code 444411310









Key features

- √ Temperature range of +2°C to +8°C
- √ Audible and visual temperature alarms
- √ Left hand hinged glass door
- ✓ Integrated lock, supplied with 2 keys for added security











Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



SKU Code	444411310
Product Code	PPGR158BT-LHH-UK
Gross Capacity (litres)	158L
Net Capacity (litres)	154L
Unit External Width (mm)	595mm
Unit External Depth (mm)	600mm
Unit External Height (mm)	850mm
Product Weight (kg)	39.75kg
Packed Width (mm)	640mm 660mm
Packed Depth (mm) Packed Height (mm)	910mm
Packed Weight (kg)	91011111 44.76kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	495mm x 480mm x 720mm
Temperature Range	+2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	PVC / Glass
Door Type	Glass
Door Style	Hinged, Left Hand, Non-Reversible
Door Liner	Glass
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor Lock	Yes Yes, 2 Keys
Adjustable Feet (number & position)	4 All adjustable
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	4
Number of Shelf Positions	5
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Size 2 (mm) (WxDxH)	493mm x 265mm x 6mm
Shelf Material	White Polythene Coated Wire
Drawer Size (mm) (WxDxH)	N/A
Drawer Size 2 (mm) (WXDXH) Drawer Material	N/A N/A
Number of Baskets	
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / App
Fan	Yes - Tangential
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	Yes/48hrs
Bluetooth	Yes
Number of Probes	2
Number of Probes Probe Type	Air & Load (Silicone Oil)
Number of Probes Probe Type Ambient Temperature Range	10°C to 32°C
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	10°C to 32°C R600a/28g
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	10°C to 32°C R600a/28g Yes
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available	10°C to 32°C R600a/28g Yes No
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply	10°C to 32°C R600a/28g Yes No 220-240V
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.92kWh/24h 328.5kWh
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.92kWh/24h 328.5kWh
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.92kWh/24h 328.5kWh 40.1dB 45mm High Density Polyurethane Foam
Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	10°C to 32°C R600a/28g Yes No 220-240V 50Hz 101W 0.78A 0.92kWh/24h 328.5kWh 40.1dB 45mm

